

Declaration of Performance

Fibrin® 660F

Adfil nv
 Industriestraat 39
 9240 Zele, Belgium
 T: +44 1482 863777
 info@adfil.com

| | | | |
|---------------|----|---------------|------|
| Factory code: | 02 | Class: | Ib |
| AVCP System: | 3 | Notified Lab: | 1136 |

Intended use: for non-structural use in mortar, grout and concrete

Product code: F5019P0631

| Essential Characteristics | Performance | Tolerance | Standard |
|---------------------------|-------------|-------------|-----------------|
| Length | 6 mm | +/-1,5 mm | EN 14889-2:2006 |
| Linear Density | 430 tex | +/-43 tex | EN 14889-2:2006 |
| Equivalent Diameter | 0,78 mm | +0,04 mm | EN 14889-2:2006 |
| Tensile strength | 110 MPa | -28 MPa | EN 14889-2:2006 |
| Tenacity | 12,2 cN/tex | -3,1 cN/tex | EN 14889-2:2006 |
| Vebe time - 0,6kg | n.p.d. | | EN 14889-2:2006 |
| Vebe time - 0,75kg | n.p.d. | | EN 14889-2:2006 |
| Vebe time - 0,9kg | 5,3 (7,0) s | | EN 14889-2:2006 |
| Vebe time - 0,91kg | n.p.d. | | EN 14889-2:2006 |
| Vebe time - 1,0kg | n.p.d. | | EN 14889-2:2006 |
| Vebe time - 1,2kg | n.p.d. | | EN 14889-2:2006 |

- n.p.d. = no performance determined

The performance of the product identified above is in conformity with the declared performance in above table.

This declaration of performance is issued under the sole responsibility of

Zele, Belgium

1/07/2013

Jeroen Smet
 Product Manager

