

## Declaration of Performance

### PC12

Low & Bonar nv  
 Industriestraat 39  
 9240 Zele, Belgium  
 T: +44 1482 863777  
 info@adfil.com

Factory code:	02	Class:	Ia
AVCP System:	3	Notified Lab:	1136

**Intended use: for non-structural use in mortar, grout and concrete**

**Product code:** M400P1212

Essential Characteristics	Performance	Tolerance	Standard
Length	12 mm	+/-1,5 mm	EN 14889-2:2006
Linear Density	11,4 dtex	+/-1,14 dtex	EN 14889-2:2006
Equivalent Diameter	40 µm	+/-2,0 µm	EN 14889-2:2006
Tensile strength	163 MPa	-41 MPa	EN 14889-2:2006
Tenacity	18 cN/tex	-4,5 cN/tex	EN 14889-2:2006
Vebe time - 0,6kg	n.p.d.		EN 14889-2:2006
Vebe time - 0,75kg	6,0 (7,0) s		EN 14889-2:2006
Vebe time - 0,9kg	n.p.d.		EN 14889-2:2006
Vebe time - 0,91kg	7,2 (7,0) s		EN 14889-2:2006
Vebe time - 1,0kg	n.p.d.		EN 14889-2:2006
Vebe time - 1,2kg	n.p.d.		EN 14889-2:2006

- n.p.d. = no performance determined

The performance of the product identified above is in conformity with the declared performance in above table.

This declaration of performance is issued under the sole responsibility of

Zele, Belgium  
 1/07/2013

Jeroen Smet  
 Product Manager